



SCB

SEGMENTED DRY SOCKET

GENERAL PURPOSE

400 Pro





Cat® 400 Pro laser welded universal material socket core bits are designed to drill a wide range of applications. In use they have long service life and fast drilling speed and can be used with or without dust extraction and also used wet or dry.

ATTRIBUTES

- **LASER WELDED - FAST AGGRESSIVE DRILLING**
- **LONG LIFE HIGH QUALITY DIAMOND GRIT & BOND FORMULATION.**

APPLICATION

★★★★	SOFT - MEDIUM AGGREGATE CONCRETE (GRANITE - LIMESTONE), TERRACOTTA, CONCRETE PAVIOURS, KERBS, SLABS, CONCRETE ROOF TILES, PIPES, SOFT FACING BRICKS, DH100:DK112 CONCRETE BLOCKS OVER 15N/MM², SOFT SLATE, MEDIUM SANDSTONE (MEDIUM GRIT), SOFT SANDSTONE (COARSE GRIT), CONCRETE SCREED, PLASTER - GROUT, CONCRETE BLOCK UNDER 15N/MM², THERMAL BLOCK 7 N/MM². ON HARDER MATERIALS USE A SLOWER PERIPHERAL SPEED RPM.
★★★	MEDIUM AGGREGATE CONCRETE (TRAPROCK - QUARTZ), CLASS B ENGINEERING BRICK 75N/MM², LIGHT REINFORCED CONCRETE, LIMESTONE AGGREGATE CONCRETE, MEDIUM FACING BRICK, HARD SLATE, MARBLE, HARD SANDSTONE (FINE GRIT), MORTAR (HARD), MORTAR (ABRASIVE).
★★	HARD TO MEDIUM AGGREGATE CONCRETE (CHERT - TRAP ROCK - RIVER GRAVEL), REFRACTORY BRICK, INDIAN STONE (KOTA), TRAVERTINE, PORPHYRY, BASALT, HARD LIMESTONE, LIGHTLY REINFORCED CONCRETE, HARD FACING BRICK, LIGNACITE BLOCKS, LAVA ROCK, PUMICE.
★	GRANITE, QUARTZITE, CRITICALLY HARD AGGREGATE CONCRETE (FLINT, CHERT), CLASS A ENGINEERING BRICK 125 N/MM², CLASS A ENGINEERING BRICK 125 N/MM².



DRY DRILLING

PRODUCT		DIAMETER		SEGMENT HEIGHT		SEGMENT WIDTH		FITTING TYPE		MACHINES USED
PART NO	CODE NO	MM	INCH	MM	INCH	MM	INCH	MM	INCH	
DA39026	SCB68M16	68	2 43/64	10	0.394	3.5	0.138	M16 F	N/A	
DA39027	SCB82M16	82	3 15/64	10	0.394	3.5	0.138	M16 F	N/A	



WARNING: This product can expose you to "Nickel" which is known to the State of California to cause cancer and birth defects.
ADVERTENCIA: Este producto puede exponerlo a un "Níquel" que el Estado de California sabe que causa cáncer y defectos de nacimiento.
AVERTISSEMENT: ce produit peut vous exposer à un "Nickel" connu de l'État de Californie pour provoquer le cancer et des malformations congénitales. www.P65Warnings.ca.gov



©2023 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. C6 DIAMOND LLC, a licensee of Caterpillar Inc.

SILICA DUST: Workers who are exposed to respirable crystalline silica dust are at increased risk of developing serious silica-related diseases. It is necessary to use saws and other machinery that is equipped with an integrated water delivery system that continuously feeds water to the blade. Operate and maintain all tools in accordance with manufacturer's instructions to minimize dust emissions and always wear the correct ventilator. For more info visit: www.osha.gov/sites/default/files/publications/OSHA3681.pdf