

USAAM80-15

SEGMENTED RIM

0.591" 15mm high

1000 Expert BEST

ASPHALT & ABRASIVE MATERIALS



Cat® Asphalt / Abrasive blades are designed for intensive use across the 3 performance grades: Good, Better and Best. Each individual product has specifically designed segments shape and geometry which complements the diamond grit and bond formulation that is proved to enhance the cutting performance in terms of fluidity and smoothness of cut, speed and blade life. Cat® Asphalt / Abrasive blades are able to cut all types of asphalt and abrasive materials. Each increase in performance rating increases the performance in terms of speed and life by use of higher diamond quality and diamond concentration, bond formulation and segment height. All blades have special undercut protection segments for clearing debris from the cut alleviating undercutting of the segments.

ATTRIBUTES

- **ULTRA HIGH DIAMOND CONCENTRATION** & DIAMOND QUALITY
- **UNDERCUT PROTECTION SEGMENTS TO CLEAR DEBRIS**
- **FULLY HARDENED & HEAT TREATED** STEEL CORE
- ULTRA LONG LIFE & SPEED OF CUT. WIDEST APPLICATION SPAN
- **ULTIMATE DIAMOND QUALITY & BOND FORMULATION**
- 2X LASER WELDED FOR SAFETY & STABILITY OF SEGMENTS
- **KEYHOLE GULLET DESIGN FOR DUST** EXTRACTION FROM CUT.



DRY CUTTING



WET CUTTING











APPLICATION



ASPHALT, CONCRETE BLOCK UNDER 15N/MM², THERMAL BLOCK 7 N/MM2, GREEN CONCRETE UNIVERSAL, GREEN CONCRETE WITH VERY HARD AGGREGATE, GREEN CONCRETE WITH MEDIUM HARD AGGREGATE.

LIGNACITE BLOCKS, LAVA ROCK, PUMICE.

ASPHALT OVER CONCRETE.

SOFT FACING BRICKS

PRODUCT TYPE		DIAMETER		SEGMENT HEIGHT		SEGMENT WIDTH		MAIN BORE		FITTED REDUCER	MACHINE USED
PART NO	CODE NO	MM	INCH	ММ	INCH	ММ	INCH	мм	INCH		
DA35622U	USAAM801215	300	12	15	0.591	3.175	0.125	25.4+P	1+P	20mm	
DA35623U	USAAM801415	350	14	15	0.591	3.175	0.125	25.4+P	1+P	20mm	
DA35624U	USAAM801615	400	16	15	0.591	3.175	0.125	25.4+P	1+P	20mm	
DA35625U	USAAM801815	450	18	15	0.591	3.175	0.125	25.4+P	1+P	20mm	
































©2023 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. C6 DIAMOND LLC, a licensee of Caterpillar Inc

SILICA DUST: Workers who are exposed to respirable crystalline silica. dust are at increased risk of developing serious silica-related diseases. It is necessary to use saws and other machinery that is equipped with an integrated water delivery system that continuously feeds water to the blade. Operate and maintain all tools in accordance with manufacturer's instructions to minimize dust emissions and always wear the correct ventilator. For more info visit: www.osha.gov/sites/default/files/publications/OSHA3681.pdf